

Gruppindelning - TRYGG FLEXI 8 & 9,5 mm

2025-10-01

602... = 8/9 mm					603... = 9,5/10,5 mm												
Varunr.	Däckd.	Bana	A	B	C	Varunr.	Däckd.	Bana	A	B	C	Varunr.	Däckd.	Bana	A	B	C
602901	12,4-28	1	1	1	1	602911	17,5-25	1	1	1	1	603907	13,6-24				
89 kg	12,4-32					92 kg	19,5L-24			1		96 kg	14,5-20	1		1	
	13,6-28			1			440/80-24		1	1	1		14,9-20			1	1
602902	11,2-24	1		1	1		480/65-24	1					14/80-20	1	1	1	1
78 kg	11,2-28						480/65-28		1	1	1		340/85-24				
	12,4-24			1			480/70-24		1	1	1		360/70-24			1	
	280/85-24	1	1	1	1		495/70-24	1					365/80-20	1		1	
	320/70-24	1					520/65-24	1					375/75-20	1	1		1
	320/85-24			1	1	603901	14,9-38						380/70-24				
602903	13,6-24	1				135 kg	15,5-38						400/70-18	1	1	1	1
87 kg	14,9-24						16,00-24/25	1					405/70-18	1		1	
	360/70-24	1	1	1	1		16,9-28	1	1	1	1	603908	20,5-25	1		1	
	380/70-24						16,9-30	1				140 kg	480/70-30	1	1	1	1
	380/85-24						16,9-34						480/70-34			1	
	400/60-26,5	1		1			18,4-26	1		1			520/70-30			1	
	400/80-24						18,4-30						540/65-30	1		1	
	425/75-20	1					420/70-34	1		1			540/65-34				
602904	12,4-20	1	1	1	1		420/85-28	x	x	x	x		600/65-28	x	x	x	x
78 kg	12,5-20	1	1	1	1		420/85-30	1	1	1	1	603909	18,4-38			1	2
	13,6-16	1	1	2	1		440/80-28	x	x	x	x	160 kg	460/85-38	x	x	x	x
	14,5-20			1	1		460/85-30			1			480/70-38	1	1	2	1
	14/80-20			1	1		480/70-30	x	x	x	x		520/70-34	1	1	1	1
	300/70-24	1	1	1	1	603902	16,9-38						520/70-38			1	
	320/70-24			1	1	145 kg	18,4-30	1		1			540/65-38	1		1	
	340/75-20	1	1	2	1		18,4-34						600/65-34	1			
	360/70-20	1		1			420/85-34	1				603910	12,4-24	1		1	
	365/80-20			1	1		460/85-30	1	1	2	1	103 kg	12,4-28			1	1
602905	8,00-20	1	2	2	2		460/85-34			1			13,6-24			1	
65 kg	8,25-20	1	2	1	2		480/70-34	1					320/85-24	1		1	
	8,3-24	1	1	1	1		480/70-38					603911	17,5-25			1	1
	9,5-20	1	1	1	1	603903	13,00-24/25	1				119 kg	19,5L-24			1	1
	9,5-24					110 kg	13,6-28	1	1	1	1		440/65-28				
602906	10,5-20	1	1	1	1		14,00-20	1					440/70-24				
69 kg	11,2-20						14,9-24	1	1	1	1		440/65-28	x	x	x	x
	12,5/80-18	1					14,9-26	1					440/80-24	1		1	
	12,5/80-20						14,9-28						480/65-24	1	1	1	1
	260/80-20	1	1	1	1		15,5-25	1	1	1	1		480/65-28				
	280/70-20	1	1	1	1		380/70-28	1					480/70-24			1	1
	300/70-20	1					380/85-24	1	1	1	1		495/70-24	1			
	320/70-20						380/85-28						500/70-24	1			
602907	16/70-20					603904	12,4-36	1	1	1	1		520/65-24	1		1	
80 kg	360/70-20	1	1	1	1	123 kg	12,4-38	1									
	365/80-20			1	1		13,6-36			1	1						
	375/75-20	1					13,6-38										
	380/70-20			1	1												
	405/70-18	1				603905	16,0/70-24	1		1							
	405/70-20					107 kg	400/80-24			1	1						
602908	10,0/75-15,3	1	1				405/70-24	1		1							
57 kg	10,5/70-15,5	1	1				420/65-24	1		1							
	10-16,5			2	1		420/70-24			1							
	12-16,5						440/65-24	1									
602909	12,5-18		2	1	2		440/65-26,5										
67 kg	14,0/65-16	1	2	2	2	För kort på	440/65-28		vissa	däck							
	400/60-15,5	1	2	2	2		440/70-24										
	15,0/55-17	1	2	1	2		445/70-24										
	15,5/55-18	1	1	1	1		455/70-20	1	1	1	1						
	15,5/65-18					603906	14,00-24/25			1	1						
	335/80-18		1	1	1	114 kg	14,9-28				2						
	340/65-18	1	1	2	1		14,9-30				1						
	365/70-18			1	1		16,9-24				1						
	38x14.00-20			1	1		16,9-26				1						
							380/85-28				2						
602910	400/80-24		1	1	1		380/85-30										
95 kg	405/70-24	1	1	1	1		420/70-28				1						
	420/70-24			1	1		420/70-30										
	420/65-24	1	1	1	1		420/85-24	1	1	1	1						
	440/65-24	1		1													
	440/65-28																
	440/65-26,5		1	1	1												
	440/70-24			1	1												
	445/65-22,5	x	x	x	x												
	445/70-24			1	1												
	460/65-24	1															
	460/70-24			1	1												
	16.0/70-24	1	1	1	1												

KEDJAN



Med tanke på olika mönster och slitage på däck, bör en ny shokedja tillpassas direkt på däck.